




HHR-70AAH/FT Cylindrical AA size (HR15/49) for back-up use

Dimensions (with tube) (mm)



Typical charge characteristics




Specifications

Diameter	14.5+0 / -0.7mm
Height	48.3+0 / -1.0mm
Approximate Weight	18g

Nominal Voltage		1.2V	
Discharge Capacity ^{*1}	Average ^{*2}	750mAh	
	Rated (min)	700mAh	
Approx. Internal impedance at 1000Hz at charged state		25mΩ	
Charge	Standard	70mA x 16hrs.	
	Rapid ^{*3}	350mA x 2.4hrs.	
	Low rate	35mA x 32hrs. 23mA x 48hrs.	
Ambient Temperature	Charge	Standard	-10°C to 60°C
		Rapid	
		Low rate	
Discharge		-10°C to 60°C	
Storage	<1 year	-20°C to 35°C	
	<6 months	35°C to 45°C	
	<1 month	45°C to 55°C	
	<1 week	55°C to 65°C	

Typical discharge characteristics



^{*1} After charging at 0.1It for 16 hours, discharging at 0.2It.
^{*2} For reference only.
^{*3} Need specially designed control system. Please contact Panasonic for details.

Battery performance and cycle life are strongly affected by how they are used. In order to maximize battery safety, please consult Panasonic when determining charge/discharge specs, warning label contents and design.

*The data in this document are for descriptive purposes only and are not intended to make or imply any guarantee or warranty.